


NON-LED

 **Wasserdichte Schraubverbindung**



Drees GmbH Sundern / GERMANY	Wasserdichte Schraubverbindung 238-470-51 238-471-51		Kategorie: NON-LED
			2018-08-16
			R002
			
Wasserdichte Schraubverbindung aus PA66GF UL90 VO GWT 960°C waterproofed screwed cable gland, material PA66GF UL90 VO GWT 960°C			
			 RoHS 2002/95/EC
IP68 			
Technische Daten / specifications:			
Beschreibung description	238-470-51	238-471-51	
Gehäusematerial case material	PA66GF UL90 VO GWT 960°C		
Gehäusefarbe case colour	schwarz black		
Abmessungen dimensions	115x26,5mm	130x32mm	
passende Kabel suitable cable	H05VV-F	H05VV-F	
Pole pole	3	5	
min Querschnitt / Durchmesser min cross-section / diameter	3G1,5mm ² / Ø7mm	5G1,5mm ² / Ø8mm	
max Querschnitt / Durchmesser max cross-section / diameter	3G4mm ² / Ø13mm	5G4mm ² / Ø17mm	
max Strom max current	32A	32A	
max Spannung max voltage	450Vac	450Vac	
max Druck max pressure	5 Bar	5 Bar	
Temperatur temperature	-40°C - 85°C	-40°C - 85°C	